



VFGL-4 Log Sets



VFST 27-2 Multi-View Log Sets

Equipped with adjustable flame height and intensity, the VFGL-4 and VFST 27-2 are 99% heat efficient and are available as manual or millivolt models in many sizes.



Believe it or not... with a simple gas line connection, vent-free gas log sets from Superior® can turn any fireplace into a clean, convenient space heater. The VFGL-4 logs are designed to be used in vent-free, full-size fireboxes, solid fuel-burning masonry or manufactured wood-burning fireplaces. The VFST 27-2 logs are designed to fit in most masonry or factory-built multi-view fireplaces (see-through and peninsula models). Each log set produces three times the heat of conventional vented gas logs for about half the cost. Their vent-free design is 99%* heat efficient with adjustable high/low settings that control heat output for consistently comfortable room temperatures. All models are design certified by OMNI Test Laboratories as room heaters.

The VFGL-4 gas log sets feature unitized rustic oak-style logs, and the VFST 27-2 logs feature charred oak. Each is made of heat-resistant, lightweight ceramic fiber, and the logs simulate real wood. The dual burners produce animated yellow flames to create a beautiful fire presentation at every angle. **Millivolt valve models have a standard on/off rocker wall switch, thermostat and hand-held remotes are optional.**

The VFGL-4 logs are available in 18", 24" and 28" lengths and the VFST 27-2 logs are available in 27" lengths. Each log set is available in natural gas or propane models.

*As tested by Lennox Hearth Products

STANDARD FEATURES

Standard on/off rocker wall switch

VFGL-4 models feature exclusive CrossLighter dual burner that maintains full rear yellow flames on both high and low manual settings – front burner turns off on low setting

One-year limited warranty

OPTIONAL ACCESSORIES

Optional wireless remote control (standard or deluxe), or wall-mounted thermostat, delivers the ultimate in flame and temperature control (millivolt valve only)



MODELS AND SPECIFICATIONS

Log Set Model Number	Valve Type	Recommended Superior Vent-Free Fireplace	BTU/hr Input
VFGL-18MSN-4	Manual†	UVF-36 / UVFRC-3628	14,000 – 25,000
VFGL-18MSP-4	Manual†	UVF-36 / UVFRC-3628	14,000 – 25,000
VFGL-24MSN-4	Manual†	UVF-36 / UVFRC-3628 / UVFRC-4228	17,000 – 32,000
VFGL-24MSP-4	Manual†	UVF-36 / UVFRC-3628 / UVFRC-4228	17,000 – 32,000
VFGL-28MSN-4	Manual†	UVFRC-4228	17,000 – 32,000
VFGL-28MSP-4	Manual†	UVFRC-4228	17,000 – 32,000
VFGL-18VSN-4	Millivolt	UVF-36 / UVFRC-3628	19,500 – 25,000
VFGL-18VSP-4	Millivolt	UVF-36 / UVFRC-3628	19,500 – 25,000
VFGL-24VSN-4	Millivolt	UVF-36 / UVFRC-3628 / UVFRC-4228	25,000 – 32,000
VFGL-24VSP-4	Millivolt	UVF-36 / UVFRC-3628 / UVFRC-4228	25,000 – 32,000
VFGL-28VSN-4	Millivolt	UVFRC-4228	25,000 – 32,000
VFGL-28VSP-4	Millivolt	UVFRC-4228	25,000 – 32,000

MODEL NUMBER DEFINITION: MN, MP, MSN, MSP, VSN or VSP

M=Manual Control Valve • N=Natural Gas • P=Propane Gas • S=Split Log Set • V=Millivolt valve for remote On/Off

Example: A log set with "MSN" indicates a manual gas valve, split oak log set and built for natural gas use.


NOTE: Sets can be installed only in a solid-fuel burning masonry, UL 127 manufactured fireplaces, or in a listed ventless firebox enclosure that has been installed according to their listing. Damper may be in the fully closed position when using vent-free log sets. Consult your dealer for local fireplace code information.

Distributed by:

MINIMUM HEARTH AREA


VFGL-4	A	B	C
18" Models	19"	14"	20"
24" Models	22"	14"	26"
28" Models	26"	14"	30"

(Minimum Height Opening: 16")



VFST 27-2	A	B
Multi-View Model	28"	18"

(Minimum Height Opening: 16")



IMPORTANT NOTES:

Diagrams, illustrations and photographs are not to scale - consult installation instructions. Product designs, materials, dimensions, specifications, colors and prices are subject to change or discontinuance without notice.

Square-foot heating capacities are approximations only. Local conditions, such as elevation, wind, vent configuration and choice of fuel will affect overall appearance of the fire and heating performance. Performance can also vary with home design and insulation, ceiling heights, climate, accessories chosen, appliance location and how the appliance is operated.

Built to ANSI Z21.11.2 Standard.

Agency Listings: OMNI Test Laboratories.



©Lennox Industries Inc. 2010

Visit us at www.Lennox.com, or contact us at 1-800-9-LENNOX.

785141M 10/10



OMNI-Test Laboratories, Inc.



100% recycled

*Manual Control Sets only are also built to ANSI Z21.60 Standard and design certified by OMNI Test Laboratories as vented log sets.