BIS® Panorama


EPA Wood Burning Fireplaces Specifications


Cat.#	Model	Description
BISPAN	BIS Panorama	EPA Wood-Burning Fireplace

Product Reference Information		
Weight	385 lbs	
Height	45"	
Width	38"	
Depth	24-1/2"	
Chimney Weight ASHT+* (7" dia)	7.8 lb/ft.	
Chimney Weight ACBI* (8" dia.)	3.75 lb/ft.	


*Available from Security Chimneys™


FRAMING DIMENSIONS			
Α	38-1/4"	972 mm	
В	47-3/8"	1203 mm	
С	30-1/16"	764 mm	
D	15-1/32"	382 mm	
E	77-1/16"	1957 mm	
F	38-17/32"	979 mm	
G	24"	610 mm	
Н	23"	504 mm	
J	54-1/2"	1384 mm	
K	8"	203 mm	
L	1"	25 mm	






Combustible materials can NOT be used in the space directly above the fireplace. Do not fill the space above the fireplace with any material (Except the wood framing)





30-1/16" 11-1/4" 13-3/8" 22-11/32" 1-1/2"

Framing Dimensions



Diagrams, illustrations and photographs are not to scale - consult installation instructions. Product designs, materials, dimensions, specifications, colors and prices are subject to change or discontinuance without notice.

Notes

All framing dimensions calculated for 1/2" dry wall at the fireplace face. If sheathing the chase or finishing with other thickness materials, calculations will need to be made.

The fireplace must not be in contact with any insulation or loose filling material. Cover the insulation with Drywall panels around the fireplace.



Listed to standards: ULC-S610 & UL-127 Report No. 192-5237


Page 1 of 2


Intertek

Fireplace Dimensions

P/N 506035-56 REV. B 05/2013

Combustible Clearances





CLEARANCE TO COMBUSTIBLES

The following clearances meet the minimum requirements for a safe installation :

Side wall: 24" (610 mm) measured from the doors edge

 $\textbf{Ceiling:} \ 6'8" \ (2032 \, mm) \, measured \, from \, the \, base \, of \, the \, fireplace$

Fireplace enclosure:

Bottom: 0"

Side: 0" to spacer 0" to spacer Back:

Do not fill the space above the fireplace with any material (7 feet measured from the base of the

fireplace)

Chimney:

ASHT+: 2" (50mm)

ACBI: 1" (25mm) at ceiling/roof level and 2" (50mm)

through a wall

Approved Chimney Types *: Use only with listed 7 in. Diameter Chimney, certified models ASHT+, S-2100+, HT6000+,

HT6103+ OR ACBI Chimney.

Mantel: 54" (1372 mm) measured from the base of the fireplace or 48" (1219) when installed with Clean Face Panel option (BPCF) and Gravity Air Kit

*Available from Security Chimneys™



