


The traditional masonry design elements include a large viewing area, and a flush-to-the-floor opening to help create the look of a real site-built masonry fireplace.

FEATURES


- ♠ Available in 32", 36" and 42" models
- Flush hearth floor design (hearth spacer not required for combustible floor installation)
- Refractory Panels available in a variety of colors and patterns
- Textured powder coat finish
- Mesh fire screens
- 4 20 year limited warranty

APPLIANCE SPECIFICATIONS



| H 22-7/16" 29 |)-1/8" | |
|---------------|----------|----------|
| | -1/0 | 36-1/8" |
| I 34-1/2" 41 | -1/8' | 18-1/4" |
| J 23-7/8" 26 | 5-3/4" 2 | 29-5/8" |
| K 29-1/2" 35 | j" | 12" |
| L 32-1/4" 36 | j-1/8" | 10" |
| M 16-5/8" 21 | -1/8" 2 | 23-1/16" |

CORNER FRAMING SPECIFICATIONS



| | VRT4032 | VRT4036 | VRT4042 | |
|---|----------|---------|---------|--|
| D | 30" | 37" | 43" | |
| E | 42-7/16" | 52" | 61" | |
| F | 35-7/8" | 42-1/2" | 49-5/8" | |
| G | 60" | 74" | 86" | |

IMPORTANT NOTES:

As with any fireplace, this appliance is extremely hot during operation. Read and understand all operating instructions before using this appliance. For further information, consult your dealer.

Local conditions, such as elevation and choice of fuel will affect overall appearance of the fire and heating performance. Performance can also vary with home design and insulation, ceiling height, accessories chosen and appliance location.

Diagrams, illustrations and photographs are not to scale — consult installation instructions. Product designs, materials, dimensions, specifications, colors and prices are subject to change or discontinuance without notice.

INTERIOR PANEL OPTIONS (REQUIRED)



White Stacked



White Herringbone



Red Herringbone



Red Stacked

VENT-FREE GAS LOGS (OPTIONAL)








LTF Series

FRAMING SPECIFICATIONS



| | VK14032 | VK14036 | VK14042 | |
|---|---------|---------|---------|--|
| Α | 36-3/4" | 40-1/2" | 44-1/2" | |
| В | 35-7/8" | 42-1/2" | 49-5/8" | |
| С | 16-1/4" | 20-3/4" | 22-5/8" | |





