WORLD SPORT PERFORMANCE SEAT SUZUKI DR650SE

Part # WS-600R/601L Installation Instructions:

Congratulations on the purchase of your new Sargent World Sport Performance Seat!

This seat is designed to fit the DR650SE with either the OEM fuel tank or the popular 4.9 gallon IMS fuel tank without any hardware changes to the seat. The new and improved mounting hardware is slotted to allow the seat to adjust to the larger 4.9 IMS fuel tanks and still look great on your machine. To install the Sargent Seat, remove the side panels and stock seat (per the owners manual instructions). Install the Sargent Seat World Sport Seat and reinstall the side panels. IMPORTANT: Be sure the tank catch tab (see fig1) at the front of the seat is engaged, by using a forward sliding motion, combined with moderate pressure on the seat opposite the catch tab during installation. **Mounting With OEM Tank: Mounting With IMS Tank:** When mounting your new Sargent Seat on a DR650SE When mounting your new Sargent Seat on a DR650SE with with an OEM tank, place the seat on the machine and the larger 4.9 gallon IMS tank, place the seat on the machine start the bolts. Once both bolts are started, just slide the and start the bolts. Once both bolts are started, just slide the seat completely forward and down so the mounting bolts seat back and up slightly so the mounting bolts are are completely to the rear of the slots before tightening completely forward in the slots before tightening (see fig 3). (see fig. 2). Mounting bolt location Mounting bolt location for OEM fuel tank For 4.9 gallon IMS fuel tank FIG. 2

SARGENT

WWW.SargentCycle.com

FIG. 3