

SVC-R 720P AHD Vehicle Camera



Safety Advice



Please unpack the box carefully and identify that all the parts are present.



Make sure you use the recommended power input. Damage caused to the camera by incorrect voltage is not covered by the warranty.



Do not attempt to open the casing to access the camera. Damage caused to the camera by tampering with the camera casing is not covered by the warranty.

What's in the boxCamera

Small screw tool



Introduction

The SVC-R is a 720P AHD Camera.

Adjusting the Camera

To adjust the angle of the dome camera, use the screw tool provided and unscrew the screws located on the sides of the camera.



To unscrew, turn anticlockwise to open the screw from the base.



Then adjust the camera by moving the lower bracket.




Specifications

SVC-R

Video System	PAL
Pick Up Element	1/4" CMOS Image Sensor
Image Signal Process	Digital Signal Processing System
Lens / Viewing Angle	3.6mm 120 degree
Number Of Pixel	1280x720
Effective Pixels	Approximately 3 Megapixel
Resolution	AHD 720P
Power Supply	DC 12 ± 1A, Aviator connector to
	MDVR
Power Consumption	80mA
Scanning System	2:1 Interlace
Sensitivity	0.01 Lux (IR 10m)
S/N Ratio	Max 62 dB
Auto Gain Control	Auto
Mirroring	Optional (BV)
White Balance	Auto
Electronic Shutter	Auto: 1/50 S to 1/100,000 S (Pal)
Output	1 Vp-p Composite Video Output, 75
	OHMS, Aviator connector to MDVR
Operating Temperature	-10°C ~ +60°C
Dimensions (HxWxD)	65 x 77 x 92 mm
Weight	280g
IP Rating	IP69









SmartWitness UK

5 The Pavilion, Amber Close, Tamworth, B77 4RP

+44(0) 1483 397005

sales@smartwiness.com

SmartWitness USA

1016 Lunt Avenue, Schaumburg, IL 60193, USA

+1 (312) 981-8774

sales.usa@smartwiness.com

SmartWitness Canada

Metrotower 2, 2600-4720 Kingsway Burnaby, BC V5H 4N2, Canada

+1 (778) 994-6670

sales.can@smartwiness.com