

# SVC-S 720P AHD Vehicle Camera





#### Safety Advice



Please unpack the box carefully and identify that all the parts are present.



Make sure you use the recommended power input. Damage caused to the camera by incorrect voltage is not covered by the warranty.



Do not attempt to open the casing to access the camera. Damage caused to the camera by tampering with the camera casing is not covered by the warranty.

### What's in the box

- Camera
- Small screw tool

#### **Introduction**

The SVC-S is a 720P AHD Camera.

It features a 2.8mm lens and has a viewing angle between 110-120°.

### Adjusting the Camera

To adjust the angle of the camera, use the screw tool provided and unscrew the screws located on the sides of the camera. There are 3 in total.



Then adjust the camera, remove the protective bracket holding it in place.



## Adjusting the Camera Continued


Then adjust the camera manually with your hand to your preferred position.



After you have completed your adjustment, replace the protective bracket




Then close the casing of the camera and screw back the screws.





#### Mounting the camera

To mount the camera, remove the screws from all sides



Drill a hole in the centre of the camera and screw it into your desired location.



Replace the camera and screw in the screws.








# **Specifications**

## SVC-S

	DAL
Video System	PAL
Pick Up Element	1/4" CMOS Image Sensor
Image Signal Process	Digital Signal Processing System
Lens / Viewing Angle	3.6mm Lens/120 Degree
Number Of Pixel	1280x720
Effective Pixels	Approximately 3 Megapixel
Resolution	AHD 720P
Power Supply	DC 12 ± 1A, Aviator Connector to MDVR
Power Consumption	80mA
Scanning System	2:1 Interlace
Sensitivity	0.01 Lux (IR 10m)
S/N Ratio	Max 50 dB
Auto Gain Control	Auto
Mirroring	Optional (BV)
White Balance	Auto
Electronic Shutter	Auto: 1/50 S to 1/100,000 S (Pal)
Output	1 Vp-p Composite Video Output, 75
	OHMS, Aviator Connector to MDVR
Operating Temperature	-10°C ~ +60°C
Dimensions (HxWxD)	63 x 77 x 89 mm
Weight	270g
IR Range	10m
Video cable length	40cm
IP Rating	IP69









SmartWitness UK

5 The Pavilion, Amber Close, Tamworth, B77 4RP

+44(0) 1483 397005

sales@smartwiness.com

SmartWitness USA

1016 Lunt Avenue, Schaumburg, IL 60193, USA

+1 (312) 981-8774

sales.usa@smartwiness.com

SmartWitness Canada

Metrotower 2, 2600-4720 Kingsway Burnaby, BC V5H 4N2, Canada

+1 (778) 994-6670

sales.can@smartwiness.com

©2016 SmartWitness PLC