



HIGHLIGHTS

Commercial Grade

Ruggedized engineering to support the harsh environments of any fleet application.

High Quality

Built with premium components to ensure excellent picture quality in any conditions.

Performance Backed

All add-on cameras come with a 2-year warranty against any manufacturer's defect.

+

- 2MP SONY CMOS SENSOR
- Digital Noise Reduction (DNR)
- DC 12V
- Easy Windshield Installation with 3M Adhesive
- Simple and Secure Angle Control
- Built-in microphone (used with CRX/CRXS only)

To learn more about proper camera installation, click [here](#).

SVA045-AM Technical Specifications



Synchronization	Internal	TV Mode	NTSC
Power Consumption		DC12V, 150mA	
Storage Temperature	-30°C ~ +80°C	Operating Temperature	-20-c- +60°C (Humidity: 10%-85% RH)
Dimensions		80.5mm(W) x 50.5mm(D) x 61.0mm(H)	
Housing Color	Black	Mirror	OFF
Image Sensor		2MP SONY CMOS SENSOR	
AGC		Off / Low / Middle / High	
Picture Elements		1920 (H) x 1080 (V)	
Video Output		AHD 2.0 (1080p@30/25fps)	
Scanning Mode		Progressive	
BLC		Off / Low / Middle / High	
Lens/Angle of View		2.45mm lens/120°	
Sensitivity		0.1 Lux	
S/N Ratio		More than 50dB AGC OFF	
Compatible Hardware Platforms		CP4S, CRXS	
Required Accessories		CP4S: SVA-05-EXT-B CRXS: SVA-05-EXT-B	
Warranty		2-year standard	