



CP-D/CP-D-A | SD Driver/Interior View Camera For use with CP4 DVR

Data Sheet

Overview

SD Driver/Interior View Camera for use with CP4 DVR. Internal use only. IR Night Vision. 130° lens. Ideal for installing on Windscreen, Dashboard or A pillar.

Specification

| | |
|-------------------------|------------------------------|
| Image Sensor | 1/3" CMOS |
| TV System | PAL/NTSC (optional) |
| Picture Elements | 1280 (H) x 960 (V) |
| Viewing Angle | 130° |
| Lens | f2.35mm Megapixel |
| Minimum Illumination | 0 Lux (IR On) |
| Scanning System | Progressive scan RGB CMOS |
| Synchronisation | Internal |
| S/N Ratio | More than 44dB (AGC Off) |
| Auto Gain Control (AGC) | Auto |
| Electronic Shutter | Auto |
| BLC | Auto |
| Infrared Spectrum | 940nm |
| Infrared LED | 6 LEDs |
| Video Output | 1V p-p, 75ohms, CVBS |
| Audio | Built-in Mic on CP-D-A model |
| Mirror | Available |
| Noise Reduction | 3D |
| Dynamic Range | 83.5 dB |
| Power Supply | 9-18V DC |
| Power Consumption | 80mA |
| Dimensions (mm) | 36(L) x 29.5 (W) x 53 (H) |
| Weight | 51g |
| Weatherproof | N/A |
| Operating Temp | -30°C to +70°C |

Head Office:

Unit 2 Valley Point,
Beddington Farm Road,
Croydon, CR0 4WP

US Office:

1016 Lunt Avenue,
Schaumburg,
IL 60193, USA

Canada Office:

Metrotower II, 2600 - 4720
Kingsway, Burnaby,
BC V5H 4N2 Canada