



SV7LCD-2-Y |

7" Colour Monitor

For use with KP1S/CP2 Dashcams

Data Sheet

Overview

7" Monitor with 10m cable, for use with KP1S/CP2 dashcams. Displays live views of additional camera connected to KP1S/CP2. Supplied with bracket for installing monitor on Dashboard or Headlining.

Specification

Screen Size:	7.0"
Screen Ratio	16:9
Back Light Luminance	LED, 300cd/m2
TV System	NTSC & PAL (automatically)
Resolution	480 x RGB x 234
OSD control	Colour, Brightness, Contrast, Volume, Language (English, German, French, Spanish, Portuguese, Italian, Dutch, Simplify Chinese)
Viewing Angle	Hor. L(60°) R(60°) Ver. UP(40°) DOWN(60°)
Image reversion	Up/Down and Left/Right
Power Consumption	5W
Power requirement	DC 12-24V
AV Inputs (Phono female)	2 video inputs
Storage temperature	-30°C to +80°C
Working temperature	-20°C to +70°C
Dimensions (mm)	189.5 x 132 x 22.5 mm (WxHxD)
Weight	368g
Other Features	4 Channel display for reversing, Full image/ 2 images/4 images adjustable (*Depends on input), Built-in speaker, Removable visor
Accessories	Remote Control, Headrest, User Manual, Bracket, Plug-in card

Head Office:

Unit 2 Valley Point,
Beddington Farm Road,
Croydon, CR0 4WP

US Office:

1016 Lunt Avenue,
Schaumburg,
IL 60193, USA

Canada Office:

Metrotower II, 2600 - 4720
Kingsway, Burnaby,
BC V5H 4N2 Canada