

The new REAL FYRE G31 three(3)-tiered burner system creates high and full-bodied flame...while using fewer BTU's than other vented burner systems.

This burner has 2 specially designed log sets...<u>PLUS</u> it is also compatible with other gas log sets from the Real Fyre Vented collection.

- Choose from a variety of **control options**:
 - 1. Electronic valve with Intermittent Pilot Ignition (IPI) and variable flame height control via remote control (-2VT)
 - 2. Electronic valve with Intermittent Pilot Ignition (IPI) and on/off remote control (-02)
 - 3. Millivolt valve standing pilot with variable flame control (-17)
 - **4.** Manual valve standing pilot with variable flame (-A)
 - 5. Match lit manual valve (natural gas only)
- Select one of the following gas log sets:
 - **A. Mountain Crest Oak(MCO)** or **Mountain Crest Split Oak(MCS)** logs designed for this burner in five(5) sizes 18", 24", 30", 33" or 39"
 - B. Charred Angel Oak(CHNA) or Charred Angel Split Oak(CHNS) in three(3) sizes 18", 24" or 30"

C. or...from the **Real Fyre Vented Gas Logs** collection:

- Charred Oak(CHD) in three(3) sizes 18/20", 24" or 30"
- Charred Split(CHS) in four(4) sizes 18/20", 24", 30" or 36"
- Charred American Oak(CHAO) in three(3) sizes 18/20", 24" or 30"
- Charred Royal English Oak(CHB) in four(4) sizes 18/20", 24", 30" or 36"

Burner Model (log set sizes)	Minimum Fireplace Size				BTU Rating			
	Width		Donth	Haight	Natural Gas		Propane Gas	
	Front	Rear	Depth	Height	High	Low	High	Low
G31-18/20 (18" or 18/20" log sets)	25"	20"	15"	16"	55k	20k	40k	21k
G31-24/30 (24" log set)	35"	25"	15"	16"	65k	21k	50k	22k
G31-24/30 (30" log set)	39"	28"	15"	16"	65k	21k	50k	22k
G31-33/39 (33" log set)	44"	32"	15"	16"	75k [†] /85k	22k	60k	23k
G31-33/39 (36" or 39" log sets)	47"	32"	15"	16"	75k [†] /85k	22k	60k	23k

[†]2VT models only



