

HONDA 2016+ AFRICA TWIN CRF1000L SARGENT WORLD SPORT MODULAR SEAT SYSTEM INSTALLATION INSTRUCTIONS

| Tools Required: NONE | Congratulations, and thank you for purchasing the Sargent World Sport Modular Seat System for your Africa Twin! This system features a front seat, a rear seat, and a rear cargo rack which can replace the rear seat. The rear components feature "tool free" installation and removal (via supplied wing- bolts) which facilitate quick and easy reconfiguration. All components may be purchased separately; some may not be included in this kit. |
|---|--|
| Front Seat Installation: | Your new Sargent seat installs exactly like your OEM seat. Refer to your Honda Owner's Manual for detailed instructions (pages 93-94 of the U.S. manual). |
| | Helpful Hint: Study and understand the OEM explanation! Front seat removal and installation can be tedious — even with the OEM seat. Take your time, being sure to carefully line up all tabs and receivers (or "prongs" and "stays," as Honda calls them) in their corresponding positions for the HIGH or LOW elevation desired. Taking a little time to study and understand the OEM recommended procedures will go a long way toward hassle-free operation. |
| Rear Seat and Cargo Rack Installation: | The Sargent rear seat and rear cargo rack installs just like the OEM rear seat. Simply remove the OEM rear seat by removing the two front bolts and pulling forward disengaging the rear tabs. Reverse this operation to install the Sargent rear seat or rear cargo rack. Secure using the OEM bolts or the wing bolts supplied by Sargent. |