## 720P AHD Mobile Reverse View Camera



### Model: SVC-R-21


Analog AHD, 1.3Mega Pixel, 12V DC



#### **Operation procedures:**

- 1. Loosen the lock screws on the sun shield, remove the mounting bracket to the suitable position.
- 2. Attach the mounting bracket to the wall or ceiling, wherever you want to install the camera. Locate a wall stud or ceiling joint and secure the base by the supplied mounting screws.
- 3. Fix the lock screw.

#### **Cable Connection:**




#### Features:


- Metal-cased mobile box with fixed lens.
- Available in black finish.
- Low power consumption.
- Easy installation on ceiling or wall, surface or flush mount.
- IP68 waterproof.
- Wide dynamic range.

#### Packing list:

| Camera              | 1 |
|---------------------|---|
| Instruction Manual  | 1 |
| Self Drilling Screw | 2 |
| Hex-key             | 1 |

# **Dimensions:**





| Dynamic range             | 120 dB             |
|---------------------------|--------------------|
| Video Output              | 1 Vp-p, 75Ω,AHD    |
| Audio Output              | Optional           |
| Lens                      | f2.1mm Megapixel   |
| Power Supply              | 12V DC±10%         |
| Power Consumption         | 255mA (Max)        |
| Dimensions (L X W<br>X H) | L69 x W76 x H78 mm |
| Net Weight                | 285g               |
| Weatherproof              | IP68               |
| Operating<br>Temperature  | -30~ +70 ° C       |

\*Specifications are subject to change without prior notice.

# **Specifications:**

-69-

| Model                      | SVC-R-21                  |
|----------------------------|---------------------------|
| Pick up Device             | Sony 1/3.2"               |
| TV System                  | PAL/NTSC (Optional)       |
| Picture Elements           | 1280 (H) x 960 (V)        |
| Sensitivity                | 0 Lux (IR LED On)         |
| Scanning System            | Progressive scan RGB CMOS |
| Synchronization            | Internal                  |
| S/N Ratio                  | More than 46dB(AGC Off)   |
| Auto Gain Control<br>(AGC) | Auto                      |
| Electronic Shutter         | Auto                      |
| Back Light<br>Compensation | Auto                      |
| Infrared Spectrum          | 940 nm                    |
| Infrared LED               | 15 LEDs                   |
| Mirror                     | Available                 |
| ICR                        | N/A                       |
| Noise Reduction            | 3D                        |