



IDV33/IDV43

DIRECT VENT GAS FIREPLACE INSERT



THE ULTIMATE IN DESIGN, ENGINEERING & QUALITY

This unit illustrated is a IDV33N Direct Vent Fireplace Insert – Natural Gas, LOGF35 Log Set – Fibre Split Oak, I33CV3BL Clean View Kit – Black.



IDV33/IDV43

DIRECT VENT GAS FIREPLACE INSERT

Convert your wood burning fireplace to gas, for a new standard of warmth, beauty, safety and convenience.



STANDARD FEATURES*

- Dual Burner with glowing embers
- Millivolt or IPI valve system allows operation during power failure with Hi-Low heat and flame adjustment
- Decorative Ash Bed
- Ceramic Glass
- On/Off Rocker switch
- Heat activated blower with variable speed control
- Bedroom and bed sitting room approval
- Mobile home, bedroom and bed sitting room approval
- Safety Screen Barrier

OPTIONAL FEATURES

Clean View Kit

Black (I33CV/I43CV1 Pewter and Copper Vein available)

Front Frame

Required for CV5 Cleanview

Surrounds for Clean View

Black (I33SR2/I43S4432 Pewter and Copper Vein available)

Surround Picture Frame for Clean View

Black

Louver Kit

Black Grills

Surrounds for Louver Kit

Black

Porcelain Reflective Liner

Brick Liner

Traditional and Herringbone (IDV43 only)

Log Set

Fibre Split Oak

Glass Tray

Ember Glass (Bronze)

Wall Mount Thermostat

Standard On/Off or Programmable

Remote Control

On/Off, Thermostat On/Off, Thermostat On/Off modulating



Safety Screen Barrier



* All gas fireplaces manufactured as of January 1, 2015 will include a Safety Screen Barrier.



THE ULTIMATE IN DESIGN, ENGINEERING & QUALITY

Unit illustrated is a IDV43 Direct Vent Insert - Natural Gas, I43CV5BL Clean View Kit - Black, I43SF1BL Door Frame, I43S4432BL Surround - Black, LOGF36 Oak Log Set, IDV36RL Traditional Brick Liner.

Model	IDV33N / IDV33NE	IDV33LP / IDV33LPE	IDV43N / IDV43NE	IDV43LP / IDV43LPE
Fuel	NATURAL	PROPANE	NATURAL	PROPANE
Input	31,000 BTU	28,500 BTU	34,250 BTU	30,000 BTU
Low	20,900 BTU	23,100 BTU	24,000 BTU	22,840 BTU
FE (P.4.1-02)	57.4%	57.9%	61 / 62%	61 / 62%
Flue Sizes	3/3"	3/3"	4/3"	4/3"



Unit illustrated is a IDV33LP Direct Vent Fireplace Insert – Propane, LOGF35 Split Fiber Oak Log Set, I33CVCV Clean View Kit – Copper Vein, I33SS1CV Surround for Clean View – Copper Vein, IDV33RL Refractory Brick Liner.




Unit illustrated is a IDV33LP Direct Vent Fireplace Insert – Propane, LOGF35 Split Fiber Oak Log Set – I33CVPW Clean View Kit – Pewter, I33SS1PW Surround for Clean View – Pewter, IDV33RL Refractory Brick Liner.




IDV43N Direct Vent Insert – Natural Gas, I43LK Louver Kit, LOGF36 Log Set, IDV36RLT Refractory Brick Liner – Traditional.

STYLING



Traditional Brick Liner RLT



Herringbone Brick Liner RLH

MINIMUM FIREPLACE OPENING (IN.)

Model	Width	Height	Depth	Model	Width	Height	Depth
IDV33	26 1/4"	21 3/8"	14 3/8"	IDV43	30 3/4"	25 5/8"	14 3/4"

LOUVER KIT AND SURROUND SIZES (IN.)

IDV33	Width	Height	IDV43	Width	Height
I33LK (Louver Kit)	34 1/2"	24 3/8"	I43LK (Louver Kit)	39"	28 3/4"
I33S3426 (Surround)	34 1/2"	26 1/2"	I43LKS1BL	39"	31 3/4"
I33S4028 (Surround)	40"	28 1/8"	I43LKS2BL	44"	32 3/8"
I33S4430 (Surround)	44"	30 5/8"	I43LKS3BL	47"	36"
I33S4535 (Surround)	45"	35"			

CLEAN VIEW AND SURROUND SIZES (IN.)

Minimum Fireplace Opening: 26 3/8" W x 21 3/8" H x 14 3/8" D

IDV33 INSERT	Width	Height	Depth
I33CV (Clean View)**	33 3/8"	23"/24 5/16"	2 1/2"
I33CV3 (Clean View)**	33 3/8"	23 1/8"/24 5/16"	4 1/8"
I33SR2 (Surround)	39"	27"	5/8"
I33SRP3 (Surround Picture Frame)	41"	31"	5/8"
I33USR4 (Surround Universal)	45"	35"	1 1/16"
I33CV5 (Clean View)	37 1/8"	25 1/4"	2 5/16"
I33BT1 (Back Trim Surround)*	39"	26"	1 1/4"
I33USR4 (Surround Universal)	45"	35"	1/16"
I33CVPF5 (Clean View Picture Frame)	37 1/8"	25 1/4"	2 5/16"
I33BTPF (Back Trim Surround)*	41"	31"	1 1/4"

* Back Trim Surround required if the fireplace opening is smaller than 29 3/8" W x 22 3/8" H x 16 1/8" D.

Note: When Using I33CV5/I33CVPF5 Clean View a Door Frame is Required.

**CV and CV3 have a tapered profile.

Minimum Fireplace Opening: 29 3/8" W x 22 3/8" H x 16 1/8" D

IDV33 INSERT	Width	Height	Depth
I33CV5 (Clean View)	37 1/8"	25 1/4"	2 5/16"
I33SR2 (Surround)	39"	27"	5/8"
I33USR4 (Surround Universal)	45"	34"	1 1/16"
I33CVPF5 (Clean View Picture Frame)	37 1/8"	25 1/4"	2 1/4"
I33SRP3 (Surround Picture Frame)	41"	31"	5/8"

Note: When Using I33CV5/I33CVPF5 Clean View a Door Frame is Required.

Minimum Fireplace Opening: 30 3/4" W x 25 5/8" H x 14 3/4" D

IDV43 INSERT	Width	Height	Depth
I43CV1 (Clean View)**	37 1/2"	27 1/4"/28 3/4"	2 1/2"
I43CV3 (Clean View)**	37 3/4"	27 3/8"/28 3/4"	4 1/8"
I43S4432 (Surround)	44"	32"	5/8"
I43US4736 (Surround Universal)	47"	36"	1 1/16"
I43SPF1 (Surround Picture Frame)	43 1/2"	33 3/8"	1 1/2"
I43CV5 (Clean View)	41 3/16"	29 1/16"	2 5/16"
I43BT4230 (Back Trim Surround)*	42"	30"	1 1/4"
I43BT4432 (Back Trim Surround)*	44"	32"	1 1/4"
I43US4736 (Surround Universal)	47"	36"	1 1/16"

* Back Trim Surround required if the fireplace opening is smaller than 33 1/2" W x 26 5/8" H x 16 5/8" D.

Note: When Using I43CV5/I43CVPF5 Clean View a Door Frame is Required.

**CV1 and CV3 have a tapered profile.

Minimum Fireplace Opening: 33 1/2" W x 26 5/8" H x 16 5/8" D

IDV43 INSERT	Width	Height	Depth
I43CV5 (Clean View)	41 3/16"	29 1/16"	2 1/4"
I43S4432 (Surround)	44"	32"	5/8"
I43US4736 (Surround Universal)	47"	36"	1 1/16"

Note: When Using I43CV5 Clean View a Door Frame is Required.



2340 Logan Avenue
Winnipeg, Manitoba, Canada R2R 2V3
Phone: (204) 632-1962 Fax: (204) 632-1960
www.kingsmanfireplaces.com

IDV33/IDV43

DIRECT VENT GAS FIREPLACE INSERT



*Components may have to be ordered separately to create a complete unit. Discuss with your local Kingsman dealer for clarification.

Kingsman Fireplaces maintains a program of continuous testing, refinement and improvements of all its products. Some aspect of units shown here may be changed at any time without notice or obligation.
Certification: The models IDV33 and IDV43 are certified for Canada/USA as a Vented Gas Fireplace Heater ANSI Z21.88-2014, CSA 2.33-2014, CGA 2.17-M91 (R2009).